

Battery Charger Specs

Specifications					Input Current:			
					208	240	480	
					240	480		
Model Number	Cell (voltage)	Battery Amp Hour Range	Phase	DC Output Current	B 208 VAC Input Voltage	C 240 VAC Input Voltage	D 480 VAC Input Voltage	Weight Lbs. (kg.)
BB80-1-06-0510	6 (12V)	380-510	1	82	8	7	3	115 (52)
BB80-1-06-0600	6 (12V)	511-600	1	96	9	8	4	117 (53)
BB80-1-12-0510	12 (24V)	380-510	1	82	15	13	6	134 (61)
BB80-1-12-0600	12 (24V)	511-600	1	96	17	15	8	143 (65)
BB80-1-12-0750	12 (24V)	601-750	1	120	22	19	9	158 (71)
BB80-1-12-0875	12 (24V)	751-875	1	140	25	22	11	165 (75)
BB80-1-18-0600	18 (36V)	510-600	1	96	25	22	11	163 (74)
BB80-1-18-0750	18 (36V)	601-750	1	120	32	27	14	187 (85)
BB80-1-24-0475	24 (48V)	380-475	1	76	26	22	11	190 (86)
BB80-3-12-0540	12 (24V)	475-540	3	87	9	8	4	176 (80)
BB80-3-12-0750	12 (24V)	541-750	3	120	13	11	5	199 (90)
BB80-3-12-0875	12 (24V)	751-875	3	140	15	13	6	212 (96)
BB80-3-12-1050	12 (24V)	876-1050	3	168	18	15	8	225 (102)
BB80-3-18-0540	18 (36V)	476-540	3	87	13	11	6	208 (94)
BB80-3-18-0750	18 (36V)	541-750	3	120	18	15	8	226 (102)
BB80-3-18-0875	18 (36V)	751-875	3	140	21	18	9	257 (116)
BB80-3-18-0965	18 (36V)	876-965	3	159	24	20	10	267 (120)
BB80-3-18-1050	18 (36V)	966-1050	3	168	25	22	11	277 (125)
BB80-3-18-1260	18 (36V)	1051-1260	3	202	31	27	13	295 (133)
BB80-3-24-0475	24 (48V)	380-475	3	76	15	13	6	226 (102)
BB80-3-24-0600	24 (48V)	475-600	3	96	19	16	8	244 (110)
BB80-3-24-0750	24 (48V)	600-750	3	120	24	21	10	277 (125)
BB80-3-24-0875	24 (48V)	751-865	3	140	28	24	12	310 (140)
BB80-3-24-1050	24 (48V)	966-1050	3	168	33	29	14	326 (148)

Supplied with a 10 ft. DC output cable and output connector.
 Dimensions W cabinet=18" width x 18" depth x 22" height X cabinet=22"width x 22" depth x 26" height.
 Please refer to Warranty Certificates for warranty information.
 UL listed & CSA certified.
 Applied Energy Solutions is an ISO 9001 Registered US Manufacturer.